SKC-PTS SEMI-AUTOMATIC / SLIP-CLUTCH CORDLESS SCREWDRIVERS


Brushless Medium Torque Battery Screwdrivers Series

SKC-PTS-120, SKC-PTS-80, SKC-PTS-50





External Dimensions (mm)



Torque Range:

1.5 - 12 Nm (13.3-106 in.lbs)

Features:

- SKC-PTS Series covers a torque range of repeatable torque accuracy is within ±10%.
- High performance, Li-ion Batteries (purchased separately).
- LED indicator warns operator of low battery capacity - the red LED will flash when 20% capacity remains and light continuously at 10%.
- Front facing LED illuminates fastening area when the trigger is pulled.
- Hi/Mid/Lo Speed Selection switch on screwdriver.
- To conserve battery life, the screwdriver goes into sleep mode when idle for more than 3 seconds.
- Charging Station (purchased separately) provides quick recharge time.

Specifications				
Model		SKC-PTS-120	SKC-PTS-80	SKC-PTS-50
Input Voltage		18V		
Torque (Nm)(in.lbs)		6-12Nm 53-106 in.lbs	4-8Nm 36-71 in.lbs	1.5-5Nm 13-44 in.lbs
Repeatable Torque Accuracy		±10%		
Torque Adjustment		23+MAX steps		
Free Speed	Hi	700	1200	2200
(r.p.m) ±10%	MID	500	900	1600
	LO	350	600	1100
Weight(kg)(lbs)		1.0kg/2.2lbs (without battery)		
Size(mm)(in)		188 x 182(mm) / 7.4 x 7.2(in) (LxH without battery)		
Applicable Battery		SKC-LB1820/SKC-LB1840		
Applicable Charge Station		SKC-P120W/SKC-P80W		
Drive Size		B W W 3/8" sq		

