

BRUSHLESS AUTO SHUT-OFF 32V ELECTRIC SCREWDRIVERS

Torque Range:

0.02-2.94 Nm (0.2-26.0 in-lbs)

Features:

- Consistent Torque Output
- Torque Accuracy $\pm 3\%$ *
- Clean, Brushless Motor Technology
- Dependable, Long Lifespan
- Requires 32VDC Power Supply
- Two Speed Selections Available
- Lever or Push Start Models
- Standard or ESD Housing Material
- Includes 2 Meter Tool Cable, Driver Bits (PH), and Torque Fixing Ring



*Factory test values - actual torque results may vary depending on the specific application, operator input, and test equipment used.

| Model (Standard Housing) | Model (w/ESD Housing) | Torque (Nm) | Torque (in-lbs) | Speed (rpm) | Start Type | Power Consum. | Weight (g)(lbs) |
|--------------------------|-----------------------|-------------|-----------------|-------------|------------|---------------|-----------------|
| SKD-BN2003L | SKD-BN2003L-ESD | 0.02-0.34 | 0.2-3.0 | 1000/700 | Lever | 25W | 385g 0.8lbs |
| SKD-BN2007L | SKD-BN2007L-ESD | 0.05-0.69 | 0.5-6.1 | 1000/700 | | | |
| SKD-BN2010L | SKD-BN2010L-ESD | 0.10-0.98 | 0.9-8.7 | 1000/700 | | | |
| SKD-BN5012L | SKD-BN5012L-ESD | 0.15-1.18 | 1.3-10.4 | 1000/700 | | | |
| SKD-BN5012LF | SKD-BN5012LF-ESD | 0.15-1.18 | 1.3-10.4 | 2000 | Push | 55W | 520g 1.1lbs |
| SKD-BN5012P | SKD-BN5012P-ESD | 0.20-1.18 | 1.8-10.4 | 1000/700 | | | |
| SKD-BN5012PF | SKD-BN5012PF-ESD | 0.20-1.18 | 1.8-10.4 | 2000 | | | |
| SKD-BN5017LF | SKD-BN5017LF-ESD | 0.29-1.67 | 2.6-14.8 | 2000 | | | |
| SKD-BN5017PF | SKD-BN5017PF-ESD | 0.29-1.67 | 2.6-14.8 | 2000 | Push | 55W | 800g 1.8lbs |
| SKD-BN5019L | SKD-BN5019L-ESD | 0.29-1.86 | 2.6-16.5 | 1000/700 | Lever | | |
| SKD-BN5019P | SKD-BN5019P-ESD | 0.29-1.86 | 2.6-16.5 | 1000/700 | Push | | |
| SKD-BN7022LF | SKD-BN7022LF-ESD | 0.49-2.16 | 4.3-19.1 | 2000 | Lever | | |
| SKD-BN7022PF | SKD-BN7022PF-ESD | 0.49-2.16 | 4.3-19.1 | 2000 | Push | 55W | 800g 1.8lbs |
| SKD-BN7030L | SKD-BN7030L-ESD | 0.98-2.94 | 8.7-26.0 | 1200/900 | Lever | | |
| SKD-BN7030P | SKD-BN7030P-ESD | 0.98-2.94 | 8.7-26.0 | 1200/900 | Push | | |

| Power Supply | SKP-32BC-60W | SKP-BE32HL |
|------------------------|--------------------------|------------------------------------|
| Use with driver models | SKD-BN2_L SKD-BN5_L/P | SKD-BN5_LF/PF SKD-BN7_L(F)/P(F) |
| Input | 100-240VAC 50/60Hz | |
| Output | 32/24VDC | |
| Dims (mm) | 145 x 60 x 35 | 195 x 76 x 56 |
| Weight (g)(lbs) | 250g/0.6lbs | 450g/1lbs |

POWER SUPPLY CONVERTS AC INPUT TO 32VDC REQ'D TO PROPERLY POWER TOOL (cETLus LISTED)

